

TEDS general purpose accelerometer

ED-786A



Benefits

- Simplifies troubleshooting
- Reduces safety risks - no more climbing on machines to verify connections
- Reduces costs for set-up and tear-down
- No need to recalibrate replacement units - data acquisition system will recalibrate itself
- Designed to integrate with wireless transmitters and receivers
 - eliminates long cables
 - reduces installation, maintenance and upgrade costs of measurement and control systems


Key features

- Contains transducer electronic data sheet (IEEE 1451 - TEDS)
- Self-identifying
- Corrosion resistant
- Ground isolated
- Rugged design
- Hermetically sealed
- ESD protection
- Reverse wiring protection

Certifications



Function	Connector pin
ground	shell
power/signal	A
common	B



Note: Due to continuous process improvement, specifications are subject to change without notice.
This document is cleared for public release.

TEDS general purpose accelerometer



ED-786A

SPECIFICATIONS

Sensitivity, $\pm 5\%$, 25° C	100 mV/g
Acceleration range	80 g peak
Amplitude nonlinearity	1%
Frequency response	$\pm 5\%$ 3 - 5,000 Hz
	$\pm 10\%$ 1 - 9,000 Hz
	± 3 dB 0.5 - 14,000 Hz
Resonance frequency	30 kHz
Transverse sensitivity, max	5% of axial
Temperature response	-50° C -5%
	+120° C +5%
Voltage source	18 - 30 VDC
Current regulating diode	2 - 10 mA
Electrical noise, equiv g	
Broadband	2.5 Hz to 25 kHz 700 μ g
Spectral	10 Hz 10 μ g/ \sqrt Hz
	100 Hz 5 μ g/ \sqrt Hz
	1000 Hz 5 μ g/ \sqrt Hz
Output impedance, max	100 Ω
Bias output voltage	12 VDC
Grounding	case isolated, internally shielded
Temperature range¹	-50 to +120° C
Vibration limit	500 g peak
Shock limit	5,000 g peak
Electromagnetic sensitivity, equiv g, max	70 μ g/gauss
Sealing	hermetic
Base strain sensitivity, max	0.0002 g/ μ strain
Sensing element design	PZT ceramic / shear
Weight	95 grams
Case material	316L stainless steel
Mounting	1/4-28 UNF tapped hole
Output connector	2 pin, MIL-C-5015 style
Mating connector	R6 type
Recommended cabling	J10 / J9T2A

Accessories supplied:

- TEDS calibration data
- SF6 mounting stud (international customers specify mounting requirements)

Notes: ¹ Temperature range is limited to -40°C to +85°C when using the IEEE 1451 - TEDS function.

Note: Due to continuous process improvement, specifications are subject to change without notice. This document is cleared for public release.