



#### Item # B1740-17, Gasketed Window Sight, With Reflector, 2" Hex, 1 1/2" NPT

Gasketed Window Sights allow visual observation of liquid levels and their condition. They can be used to display fluid motion or mechanical movements, as well as to view and perform tests in a safe enclosure. Specific uses include fluid sighting on hydraulic tanks, pressure vessels, reservoirs, packaged power equipment, hydraulic lines and dipping. Their use can be applied to any application where oil or fluid inspection is essential. Two or more sights can be mounted so as to indicate high, low or in-between levels.

This window sight may be mounted into any corresponding pipe thread. It withstands up to 50 PSI and 225° F.

The body of the window sight is constructed of plated steel. The glass viewing sight is secured by a brass retaining ring. A Buna-N o-ring creates a leak tight seal. A nylon washer is seated between the retaining ring and sight to prevent glass abrasion. A stainless steel reflector maximizes liquid level visibility, even in poor light. The reflector will not tarnish, corrode or discolor under the most adverse of conditions.

This unit features a 1 1/2" male NPT mounting thread. It has a 2" hex and 1 17/32" sight diameter. When tightly secured, it extends about 17/32" from the mounting surface.

Other body materials, Viton, and EPDM seals are available upon request.

#### Specifications

Thread Type	Tapered
Thread Size	1 1/2" NPT
Hex Size	2" Hex
Sight	1 17/32" dia
Reflector	Stainless Steel
Feature	Buna-N Seal
Body	Plated Steel
Max Pressure	50 PSI