

USB VGA over Cat5 UTP KVM Console Extender Kit - 500 ft. (152.4 m)

MODEL NUMBER: 0DT60001



Features

- Compatible with any KVM switch / computer
- Extends console (USB keyboard, USB mouse and VGA monitor) up to 150m / 500ft from computer, KVM or server
- Integrated local port for local keyboard, mouse and monitor
- 2 port KVM switch built into remote unit
- Pure hardware solution - no software/network conflicts
- Supports high-resolution video - up to 1600 x 1200 @ 75 Hz
- All cables included - off-the-shelf retail package, easy to maintain
- Simple to install and operate
- No external power needed at transmitter end
- Supports all major OS
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Highlights

- Extends the VGA video and USB keyboard/mouse from your computer or KVM switch
- Console ports on both the transmitter and receiver units allow for local or remote control of the connected computer / KVM switch
- Receiver unit doubles as a 2-port KVM switch, allowing for the connection of a local computer
- Supports video resolutions up to 1600 x 1200 @ 75 Hz

System Requirements

- Compatible with all major operating systems
- Compatible with any KVM switch / computer
- USB Keyboard and Mouse
- PS/2 Keyboard and Mouse with 0DT60002 PS/2 to USB Converter
- When using the 0DT60001 to extend the console ports of a KVM switch, the transmitter unit may require an external power supply. Use a 12VDC 1A power supply.

Package Includes

- Local Transmitter Unit
- Remote Receiver Unit
- (x2) VGA + USB KVM Cable Kits
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz Output: 12V/1000mA) and Plug Adapters for US, UK, Europe and Australia, NEMA
- Screwdriver
- Rubber Feet
- Owner's Manual

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 654518302196 |

| | |
|--|--|
| Accessory Type | Extender Kit |
| Technology | VGA/SVGA |
| Accessory Class | KVM Switch Accessories |
| VIDEO | |
| Max Supported Video Resolution | 1600 x 1200 @75Hz |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 127; 200; 208; 220; 230; 240 |
| Bus Powered | Yes |
| POWER | |
| External Power Supply Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 0.5A |
| External Power Supply Output Specs (V / A) | 12V / 1A |
| External Power Supply Cord Length (ft.) | 6 |
| External Power Supply Cord Length (m.) | 1.8 |
| Power Consumption (Watts) | 12 |
| External Power Supply Plug(s) | NEMA 5-15P North America; CEE 7/16 Schuko; BS 1363 UK; AS/NZS 3112 Australia |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | TX: Green (Control), Red (Lock) RX: Green (Local), Red (Lock) |
| PHYSICAL | |
| Color | Gray |
| Material of Construction | Steel |
| Receiver Unit Dimensions (hwd / cm.) | 2.9 x 6.9 x 16.5 |
| Receiver Unit Dimensions (hwd / in.) | 1.1 x 2.7 x 6.5 |
| Receiver Unit Weight (kg) | 0.28 |
| Receiver Unit Weight (lbs.) | 0.61 |
| Shipping Dimensions (hwd / in.) | 4.10 x 8.00 x 12.40 |
| Shipping Dimensions (hwd / cm) | 10.41 x 20.32 x 31.50 |
| Shipping Weight (lbs.) | 3.80 |
| Shipping Weight (kg) | 1.72 |
| Transmitter Unit Dimensions (hwd / cm.) | 2.9 x 6.9 x 16.5 |

| | |
|---|--|
| Transmitter Unit Dimensions (hwd / in.) | 1.1 x 2.7 x 6.5 |
| Transmitter Unit Weight (kg) | 0.27 |
| Transmitter Unit Weight (lbs.) | 0.58 |
| Unit Packaging Type | Box |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 104 F (0 to 40 C) |
| Storage Temperature Range | -40 to 158 F (-40 to 70 C) |
| Relative Humidity | 0% to 80% RH, Non-Condensing |
| BTUs | 40.9 BTU/Hr |
| COMMUNICATIONS | |
| Signal Range (ft.) | 500 |
| Signal Range (m) | 152 |
| EDID Compatible | Yes |
| CONNECTIONS | |
| Number of Ports | 2 |
| PC/Server Connections | VGA; USB; PS/2 |
| Side A - Connector 1 | (2) HD15 (FEMALE); RJ45 (FEMALE); (2) USB A (FEMALE) |
| Side B - Connector 1 | (2) HD15 (FEMALE); RJ45 (FEMALE); (2) USB A (FEMALE) |
| Connector Plating | Nickel |
| FEATURES & SPECIFICATIONS | |
| Port Selection | Pushbutton |
| Recommended Category Cable | Cat5/Cat5e/Cat6 |
| IP68 Rated | No |
| IP20 Rated | No |
| STANDARDS & COMPLIANCE | |
| External Power Supply Certifications | CE; UL; CCC; PSE; C-Tick; GS; RoHS |
| Product Certifications | ICES (Canada); C-Tick (Australia) |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: