



—
your partner
in sensor
technology.



Datasheet EE850

**CO₂, Humidity and Temperature
Duct Sensor**



EE850

CO₂, Humidity and Temperature Duct Sensor

The EE850 combines CO₂, relative humidity (RH) and temperature (T) measurement in an innovative enclosure. It is ideal for demand controlled ventilation and building automation. Due to the CO₂ measuring range up to 10 000 ppm and T working range -20...+60 °C (-4...+140 °F), the EE850 can be employed also in demanding climate and process control.

Long-Term Stability

The EE850 incorporates the E+E dual wavelength NDIR CO₂ sensor, which compensates for ageing effects, is highly insensitive to pollution and offers outstanding long term stability. The RH sensing element is protected against dust, dirt and corrosion by the E+E proprietary coating.

High Measurement Accuracy

A multiple point CO₂ and T factory adjustment procedure leads to excellent CO₂ measurement accuracy over the entire T working range.

Functional Design

Installed into a duct, a small amount of air flows through the divided probe to the CO₂ sensing cell located inside the transmitter enclosure and back into the duct. The RH and T sensing elements are placed inside the probe. The functional enclosure facilitates easy and fast mounting of the transmitter with closed cover.

Analogue, Digital and Passive T Outputs

The CO₂, RH and T measured data as well as the calculated dew point temperature (Td) are available on various analogue outputs. Additionally, the RS485 interface with Modbus RTU or BACnet MS/TP protocol supplies also other parameters such as absolute humidity (dv), mixing ratio (r), water vapor partial pressure (e) or enthalpy (h).


Easy Configuration and Adjustment

An optional adapter and the free EE-PCS configuration software facilitate the configuration and adjustment of the EE850.



EE850 duct mount

Features




Test report

According to DIN EN 10204-2.2

Features



Protective Sensor Coating

The E+E proprietary sensor coating is a protective layer applied to the sensing elements, their leads and soldering points. The coating substantially extends sensor lifetime and ensures optimal measurement performance in corrosive environment (salts, off-shore applications). Additionally, it improves the sensors' long term stability in dusty, dirty or oily applications by preventing stray impedance caused by deposits on the active sensor surface or on the electrical connections.




Dimensions

Values in mm (inch)



Mounting flange



Recommended mounting screws:
ST4.2x50 DIN 7981 C

Technical Data

Measurands

CO₂

Measurement principle	Dual wavelength non-dispersive infrared technology (NDIR)
Measuring range	0...2 000 / 10 000 ppm
Accuracy @ 25 °C (77 °F) and 1013 mbar (14.7 psi) 0...2 000 ppm 0...10 000 ppm	< ±(50 ppm +2 % of measured value) < ±(100 ppm +5 % of measured value)
Temperature dependency, typ. in the range of -20...45 °C (-4...113 °F)	±(1+ CO ₂ Konzentration [ppm] / 1 000) ppm/°C
Response time t ₆₃ , typ.	< 100 s at 3 m/s (590 ft/min) air speed in the duct
Measuring interval	Approx. 15 s
Calibration interval Recommended under normal operating conditions in building automation.	> 5 years

Temperature (T)

Measuring range	-20...+60 °C (-4...+140 °F)
Accuracy @ 24 V DC, 20 °C (68 °F)	±0.3 °C (± 0.5 °F)
Response time t ₆₃	< 50 s

Relative humidity (RH)

Measuring range	0...95 %RH
Accuracy @ 20 °C (68 °F)	±3 %RH (20...80 %RH)
Response time t ₆₃	< 10 s

Outputs

Analogue

RH: 0...100 % T: according to ordering guide	0 - 10 V	-1 mA < I _L < 1 mA	I _L = load current
CO ₂ 0...2 000 / 10 000 ppm	0 - 10 V 4 - 20 mA	-1 mA < I _L < 1 mA R _L < 500 Ω	R _L = load resistance

T sensor passive




2-wire-connection	T sensor type according ordering guide
Wire resistance (terminal - sensor), typ.	0.4 Ω

Digital

Digital Interface	RS485 (EE850 = 1/10 unit load)
Protocol Factory settings Supported Baud rates Measured data types	Modbus RTU 9 600 Baud, parity even, 1 stop bit, Modbus address 67 9 600, 19 200 und 38 400 FLOAT32 and INT16
Protocol Factory settings Supported Baud rates	BACnet MS/TP BACnet address 67 9 600, 19 200, 38 400, 57 600, 76 800 und 115 200

Technical Data

General

Power supply class III  USA & Canada: Class 2 supply necessary, max. voltage 30 V DC		24 V DC $\pm 20\%$ 15 - 35 V DC		
Current consumption , typ.		15 mA + output current		
Peak current , max..		350 mA für 0.3 s (analogue output) 150 mA for 0.3 s (RS485 interface)		
Minimum air speed in the duct , min.		1 m/s (196 ft/min)		
Electrical connection		Screw terminals max. 2.5 mm ² (AWG 14)		
Cable gland		M16x1.5		
Working and storage conditions		-20...+60 °C (-4...+140 °F) 0...95 %RH, non-condensing		
Enclosure material		Polycarbonate (PC), UL94 V-0 approved		
Protection rating	Enclosure Probe	IP65/NEMA 4X IP20		
Electromagnetic compatibility		EN 61326-1 FCC Part15 Class A	EN 61326-2-3 ICES-003 Class A	Industrial environment
Conformity		EN 45545-2 (HL3)	 	

Ordering Guide

Feature		Description	Code		
Hardware Configuration			EE850-		
	Model	CO ₂	M10		
		CO ₂ + T		M11	
		CO ₂ + T + RH			M12
	CO ₂ measuring range	0...2 000 ppm	HV1		
		0...10 000 ppm	HV3		
	Output	0 - 10 V	A3	A3	A3
		4 - 20 mA	A6		
		RS485	J3	J3	J3
	T sensor passive ¹⁾	Without T sensor		No code	
		Pt1000 DIN A		TP3	
Setup Analogue Outputs ¹⁾	Probe length	50 mm (1.97")	L50		
		200 mm (7.87")	No code	No code	No code
	Output 2 measurand	Temperature T [°C]		No code	No code
		Temperature T [°F]		MB2	MB2
	Output 2 scaling low	0		No code	No code
		Value - within the range -20...60 °C		SBLValue	SBLValue
	Output 2 scaling high	50		No code	No code
		Value - within the range -20...60 °C		SBHValue	SBHValue
	Output 3 measurand	Relative humidity RH [%]			No code
		Dew point Td [°C]			MC52
		Dew point Td [°F]			MC53
	Output 3 scaling low	0			No code
		Value - for Td: within the range -20...60 °C (-4...140 °F)			SCLValue
	Output 3 scaling high	100			No code
		Value - for Td: within the range -20...60 °C (-4...140 °F)			SCHValue
Setup RS485 ⁴⁾	Protocol	Modbus RTU ²⁾	P1		
		BACnet MS/TP ³⁾	P3		
	Baud rate	9 600	BD5		
		19 200	BD6		
		38 400	BD7		
		57 600 (only for BACnet)	BD8		
		76 800 (only for BACnet)	BD9		
		115 200 (only for BACnet)	BD10		

- 1) Not with RS485 output (J3) or 50 mm probe length (L50) / T-Sensor details see _____.
- 2) Factory setting: Parity even, 1 stop bit; Modbus Map and communication setting: See User Manual and Modbus Application Note at _____.
- 3) Product Implementation Conformance Statement (PICS) available at _____.
- 4) Not with analogue output A3 und A6.

Order Example

EE850-M12HV1A3MB2SBL32SBH140

Feature	Code	Description
Model	M12	CO ₂ + T + RH
CO ₂ measuring range	HV1	0...2 000 ppm
Output	A3	0 - 10 V
Probe length	No code	200 mm (7.87")
Output 2 measurand	MB2	Temperature T [°F]
Output 2 scaling low	SBL32	32 °F
Output 2 scaling high	SBH140	140 °F
Output 3 measurand	No code	Relative humidity RH [%]
Output 3 scaling low	No code	0 %
Output 3 scaling high	No code	100 %

EE850-M10HV1A6L50

Feature	Code	Description
Model	M10	CO ₂
CO ₂ measuring range	HV1	0...2 000 ppm
Output	A6	4 - 20 mA
Probe length	L50	50 mm (1.97")

EE850-M12HV3J3P1BD6

Feature	Code	Description
Model	M12	CO ₂ + T + RH
CO ₂ measuring range	HV3	0...10 000 ppm
Output	J3	Digital interface RS485
Probe length	No code	200 mm (7.87")
Protocol	P1	Modbus RTU
Baud rate	BD6	19 200

Accessories

For further information see datasheet _____.

Accessories	Code
Configuration adapter cable	HA011066
E+E Product configuration software (Free download: _____)	EE-PCS
Power supply adapter	V03