

RB Three-Way Valves with Actuator (PN 16)

Gunmetal three-way valve with male threads and screw fitting connections in accordance with DIN, airtight.

With motor-driven actuator.

Note:

Control valves with special Kvs value and actuator available on request.

RB25MD200Y



RB Three-Way Valves with MD200 Actuator (PN 16)

	DN	kvs	Δp (bar)	Weight (kg)	Connection	Positioning time (s)
RB15/0,63MD200	15	0.63	16	2.2	G1/2"	108
RB15/1,0MD200	15	1.0	16	2.9	G1/2"	108
RB15/1,25MD200	15	1.25	16	2.9	G1/2"	108
RB15/1,6MD200	15	1.6	16	2.2	G1/2"	108
RB15/2,5MD200	15	2.5	16	2.2	G1/2"	108
RB15MD200	15	4.0	16	2.2	G1/2"	108
RB20MD200	20	6.3	16	2.7	G3/4"	108
RB25MD200	25	10	12.7	2.9	G1"	126
RB32MD200	32	16	7.8	4.6	G1 1/4"	126
RB40MD200	40	25	4.9	5.3	G1 1/2"	126
RB50MD200	50	40	3.0	6.7	G2"	126

RB Three-Way Valves with MD200Y Actuator (PN 16)

	DN	kvs	Δp (bar)	Weight (kg)	Connection	Positioning time (s)
RB15/0,63MD200Y	15	0.63	16	2.2	G1/2"	108
RB15/1,0MD200Y	15	1.0	16	2.2	G1/2"	108
RB15/1,25MD200Y	15	1.25	16	2.2	G1/2"	108
RB15/1,6MD200Y	15	1.6	16	2.2	G1/2"	108
RB15/2,5MD200Y	15	2.5	16	2.2	G1/2"	108
RB15MD200Y	15	4.0	16	2.2	G1/2"	108
RB20MD200Y	20	6.3	16	2.7	G3/4"	108
RB25MD200Y	25	10	12.7	2.9	G1"	126
RB32MD200Y	32	16	7.8	4.6	G1 1/4"	126
RB40MD200Y	40	25	4.9	5.3	G1 1/2"	126
RB50MD200Y	50	40	3.0	6.7	G2"	126

RB Three-Way Valves with MD200BUS Actuator (PN 16)

	DN	kvs	Δp (bar)	Weight (kg)	Connection	Positioning time (s)
RB15/0,63MD200BUS	15	0.63	16	2.2	G1/2"	111
RB15/1,0MD200BUS	15	1.0	16	2.2	G1/2"	111
RB15/1,25MD200BUS	15	1.25	16	2.2	G1/2"	111
RB15/1,6MD200BUS	15	1.6	16	2.2	G1/2"	111
RB15/2,5MD200BUS	15	2.5	16	2.2	G1/2"	111
RB15MD200BUS	15	4.0	16	2.2	G1/2"	111
RB20MD200BUS	20	6.3	16	2.7	G3/4"	111
RB25MD200BUS	25	10	12.7	2.9	G1"	130
RB32MD200BUS	32	16	7.8	4.5	G1 1/4"	130
RB40MD200BUS	40	25	4.9	5.0	G1 1/2"	130
RB50MD200BUS	50	40	3.0	6.5	G2"	130

RB...BK Two-Way Valves with Actuator (PN 16)

Gunmetal three-way valve with blank cover. Male threads and screw fitting connections in accordance with DIN, airtight.

With motor-driven actuator.

Note:

Control valves with special Kvs value and actuator available on request.

RB...BK Two-Way Valves with MD200 Actuator (PN 16)

	DN	kvs	Δp (bar)	Weight (kg)	Connection	Positioning time (s)
RB15/0,63-BKMD200	15	0.63	16	2.2	G1/2"	108
RB15/1,0-BKMD200	15	1.0	16	2.2	G1/2"	108
RB15/1,25-BKMD200	15	1.25	16	2.2	G1/2"	108
RB15/1,6-BKMD200	15	1.6	16	2.2	G1/2"	108
RB15/2,5-BKMD200	15	2.5	16	2.2	G1/2"	108
RB15-BKMD200	15	4.0	16	2.2	G1/2"	108
RB20-BKMD200	20	6.3	16	2.7	G3/4"	108
RB25-BKMD200	25	10	12.7	2.9	G1"	126
RB32-BKMD200	32	16	7.8	4.6	G1 1/4"	126
RB40-BKMD200	40	25	4.9	5.2	G1 1/2"	126
RB50-BKMD200	50	40	3.0	6.5	G2"	126

RB...BK Two-Way Valves with MD200Y Actuator (PN 16)

	DN	kvs	Δp (bar)	Weight (kg)	Connection	Positioning time (s)
RB15/0,63-BKMD200Y	15	0.63	16	2.2	G1/2"	108
RB15/1,0-BKMD200Y	15	1.0	16	2.2	G1/2"	108
RB15/1,25-BKMD200Y	15	1.25	16	2.2	G1/2"	108
RB15/1,6-BKMD200Y	15	1.6	16	2.2	G1/2"	108
RB15/2,5-BKMD200Y	15	2.5	16	2.2	G1/2"	108
RB15-BKMD200Y	15	4.0	16	2.2	G1/2"	108
RB20-BKMD200Y	20	6.3	16	2.7	G3/4"	108
RB25-BKMD200Y	25	10	12.7	2.9	G1"	126
RB32-BKMD200Y	32	16	7.8	4.6	G1 1/4"	126
RB40-BKMD200Y	40	25	4.9	5.2	G1 1/2"	126
RB50-BKMD200Y	50	40	3.0	6.5	G2"	126

RB..-BK Two-Way Valves with MD200BUS Actuator (PN 16)

	DN	kvs	Δp (bar)	Weight (kg)	Connection	Positioning time (s)
RB15/0,63-BKMD200BUS	15	0.63	16	2.2	G1/2"	111
RB15/1,0-BKMD200BUS	15	1.0	16	2.2	G1/2"	111
RB15/1,25-BKMD200BUS	15	1.25	16	2.2	G1/2"	111
RB15/1,6-BKMD200BUS	15	1.6	16	2.2	G1/2"	111
RB15/2,5-BKMD200BUS	15	2.5	16	2.2	G1/2"	111
RB15-BKMD200BUS	15	4.0	16	2.2	G1/2"	111
RB20-BKMD200BUS	20	6.3	16	2.7	G3/4"	111
RB25-BKMD200BUS	25	10	12.7	2.9	G1"	130
RB32-BKMD200BUS	32	16	7.8	4.5	G1 1/4"	130
RB40-BKMD200BUS	40	25	4.9	5.0	G1 1/2"	130
RB50-BKMD200BUS	50	40	3.0	6.5	G2"	130