



SLS-3200

SANTEC LCD monitor 32" (81.2 cm)
1920 x 1080, incl. remote, Non-reflecting glass

PRODUCT DESCRIPTION

► Application:

The new monitors of the SLS series have a timeless design and are equipped with professional technology.

► Technical specifications:

| | |
|-----------------------------------|----------------------|
| Type | Lcd monitor |
| Screen diagonal | 32" (81.2 cm) |
| Video signal | PAL, NTSC |
| Resolution pixel | 1920x1080 |
| TVL | > 650 |
| Picture format | 16:9 |
| Colours | 16.7M |
| Brightness (cd/m2) | 500 |
| Contrast ratio | 6000:1 |
| View angle R/L and U/D in ° | 176/176 |
| Background lighting | LED |
| Video inputs | 2 x BNC 1 x Y/C |
| Video outputs (BNC) | 2 x BNC |
| PC video input | VGA, HDMI |
| Resolution PC video input | 1920x1080 Full HD |
| 3D comb filter | Yes |
| 3D De-Interlace | Yes |
| POP (picture-on-picture) function | Video / PC |
| PIP (picture-in-picture) function | Video / PC |
| Audio inputs | 1 x Cinch, 1 x 3.5mm |

► Technical specifications:

| | |
|-------------------------------|-------------------------------|
| Speakers | 2 |
| OSD menu languages | Multi language |
| Control OSD | Buttons on rear side |
| Front screen | Clear glass, hardened |
| Installation option | VESA 200x200 |
| Housing colour | Black |
| Housing material | Metal |
| Voltage | 100 - 240 V AC |
| Max. Power consumption (watt) | < 70 / Standby < 1 |
| Operating temperature (°C) | 0 to +50 |
| Storage temperature (°C) | -20 to +60 |
| Rel. humidity (%) | 10 - 85 |
| MTBF (Panel) | 50.000 hrs. |
| 24/7 operation | Yes |
| Dimensions WxHxD (mm) | 750.5x459.7x67.5 |
| Weight | 16 kg |
| Identifier | CE |
| Items included in delivery | IR-RC, power cable, VGA cable |
| Specials | Stand |

► Note:

SECOND-HAND EQUIPMENT ONLY!

► Recommended Accessories