

# Compression Springs



FLEXO STOCK NUMBER	Range	METRIC UNITS						IMPERIAL UNITS						No of Coils	PRICE BAND
		Outside Dia.	Inside Dia.	Free Lth.	Wire Size	Solid Lth.	Rate	Outside Dia.	Inside Dia.	Free Lth.	Wire Size	Solid Lth.	Rate		
		mm	mm	mm	mm	mm	N/mm	inches	inches	inches	inches	inches	Lbs/in	approx	
163616	C 4	11.6	7.5	50.8	2.03	30.5	14.84	0.457	0.297	2.000	0.080	1.200	84.7	15.0	F
M245712	C 4	12.0	9.6	60.0	1.22	18.9	1.29	0.472	0.376	2.362	0.048	0.744	7.4	15.5	E
M245912	C 4	12.0	9.2	60.0	1.42	25.6	2.14	0.472	0.360	2.362	0.056	1.008	12.2	18.0	E
M246112	C 4	12.0	8.7	60.0	1.63	30.5	3.71	0.472	0.344	2.362	0.064	1.200	21.2	18.8	F
M246212	C 4	12.0	8.6	60.0	1.70	32.3	4.46	0.472	0.339	2.362	0.067	1.272	25.4	19.0	F
163120	C 4	12.1	10.1	63.5	1.02	13.7	0.67	0.476	0.396	2.500	0.040	0.540	3.9	13.5	D
163220	C 4	11.9	9.5	63.5	1.22	17.7	1.44	0.469	0.373	2.500	0.048	0.696	8.2	14.5	E
163320	C 4	12.1	9.3	63.5	1.42	21.3	2.56	0.476	0.364	2.500	0.056	0.840	14.6	15.0	E
163420	C 4	12.0	8.7	63.5	1.63	26.0	4.43	0.472	0.344	2.500	0.064	1.024	25.3	16.0	F
163520	C 4	11.7	8.0	63.5	1.83	31.6	7.54	0.461	0.317	2.500	0.072	1.246	43.0	17.3	F
163620	C 4	11.6	7.5	63.5	2.03	37.6	11.69	0.457	0.297	2.500	0.080	1.480	66.8	18.5	F
M245714	C 4	12.0	9.6	70.0	1.22	21.8	1.10	0.472	0.376	2.756	0.048	0.859	6.3	17.9	E
M245914	C 4	12.0	9.2	70.0	1.42	29.5	1.83	0.472	0.360	2.756	0.056	1.162	10.4	20.8	F
M246114	C 4	12.0	8.7	70.0	1.63	35.4	3.14	0.472	0.344	2.756	0.064	1.392	17.9	21.8	F
M246214	C 4	12.0	8.6	70.0	1.70	37.8	3.74	0.472	0.339	2.756	0.067	1.489	21.4	22.3	F
163124	C 4	12.1	10.1	76.2	1.02	16.3	0.55	0.476	0.396	3.000	0.040	0.640	3.2	16.0	E
163224	C 4	11.9	9.5	76.2	1.22	20.7	1.20	0.469	0.373	3.000	0.048	0.816	6.8	17.0	E
163324	C 4	12.1	9.3	76.2	1.42	25.5	2.09	0.476	0.364	3.000	0.056	1.002	12.0	17.9	F
163424	C 4	12.0	8.7	76.2	1.63	30.5	3.71	0.472	0.344	3.000	0.064	1.200	21.2	18.8	F
163524	C 4	11.7	8.0	76.2	1.83	37.3	6.27	0.461	0.317	3.000	0.072	1.469	35.8	20.4	F
163624	C 4	11.6	7.5	76.2	2.03	44.2	9.77	0.457	0.297	3.000	0.080	1.740	55.8	21.8	G
M245716	C 4	12.0	9.6	80.0	1.22	24.6	0.96	0.472	0.376	3.150	0.048	0.969	5.5	20.2	E
M245916	C 4	12.0	9.2	80.0	1.42	33.4	1.59	0.472	0.360	3.150	0.056	1.316	9.1	23.5	F
M246116	C 4	12.0	8.7	80.0	1.63	40.2	2.73	0.472	0.344	3.150	0.064	1.584	15.6	24.8	F
M246216	C 4	12.0	8.6	80.0	1.70	42.9	3.26	0.472	0.339	3.150	0.067	1.690	18.6	25.3	F
163128	C 4	12.1	10.1	88.9	1.02	18.8	0.47	0.476	0.396	3.500	0.040	0.740	2.7	18.5	E
163228	C 4	11.9	9.5	88.9	1.22	23.8	1.03	0.469	0.373	3.500	0.048	0.936	5.9	19.5	E
163328	C 4	12.1	9.3	88.9	1.42	29.3	1.79	0.476	0.364	3.500	0.056	1.153	10.2	20.6	F
163428	C 4	12.0	8.7	88.9	1.63	35.4	3.14	0.472	0.344	3.500	0.064	1.392	17.9	21.8	F
163528	C 4	11.7	8.0	88.9	1.83	43.3	5.31	0.461	0.317	3.500	0.072	1.707	30.3	23.7	G
163628	C 4	11.6	7.5	88.9	2.03	51.3	8.30	0.457	0.297	3.500	0.080	2.020	47.4	25.3	G
M245720	C 4	12.0	9.6	100.0	1.22	30.4	0.76	0.472	0.376	3.937	0.048	1.195	4.4	24.9	F
M245920	C 4	12.0	9.2	100.0	1.42	41.6	1.26	0.472	0.360	3.937	0.056	1.638	7.2	29.3	F
M246120	C 4	12.0	8.7	100.0	1.63	50.0	2.16	0.472	0.344	3.937	0.064	1.968	12.3	30.8	G
M246220	C 4	12.0	8.6	100.0	1.70	53.1	2.59	0.472	0.339	3.937	0.067	2.092	14.8	31.3	G
163132	C 4	12.1	10.1	101.6	1.02	21.1	0.41	0.476	0.396	4.000	0.040	0.832	2.4	20.8	F
163232	C 4	11.9	9.5	101.6	1.22	26.8	0.90	0.469	0.373	4.000	0.048	1.056	5.1	22.0	F
163332	C 4	12.1	9.3	101.6	1.42	32.7	1.59	0.476	0.364	4.000	0.056	1.288	9.1	23.0	F
163432	C 4	12.0	8.7	101.6	1.63	39.8	2.76	0.472	0.344	4.000	0.064	1.568	15.7	24.5	G
163532	C 4	11.7	8.0	101.6	1.83	49.0	4.65	0.461	0.317	4.000	0.072	1.930	26.6	26.8	G
163632	C 4	11.6	7.5	101.6	2.03	57.9	7.28	0.457	0.297	4.000	0.080	2.280	41.6	28.5	H
C5-3443-2M	C 5	12.7	10.7	17.5	1.02	4.8	2.41	0.500	0.420	0.689	0.040	0.190	13.8	4.7	C
C5-3447-2M	C 5	12.7	10.3	17.5	1.22	6.3	4.52	0.500	0.404	0.689	0.048	0.249	25.8	5.2	C
C5-3451-2M	C 5	12.7	9.9	17.5	1.42	7.9	8.02	0.500	0.388	0.689	0.056	0.309	45.8	5.5	D
C5-3454-2M	C 5	12.7	9.4	17.5	1.63	9.3	13.65	0.500	0.372	0.689	0.064	0.367	78.0	5.7	D
C5-3643-2M	C 5	12.7	10.7	19.1	1.02	5.1	2.19	0.500	0.420	0.750	0.040	0.201	12.5	5.0	C
173206	C 5	12.7	10.3	19.1	1.22	6.2	4.67	0.500	0.404	0.750	0.048	0.245	26.6	5.1	C
173306	C 5	12.9	10.1	19.1	1.42	8.0	7.45	0.508	0.396	0.750	0.056	0.314	42.5	5.6	D
173406	C 5	12.7	9.4	19.1	1.63	9.4	13.43	0.500	0.372	0.750	0.064	0.371	76.7	5.8	D
173506	C 5	12.6	8.9	19.1	1.83	10.5	23.67	0.496	0.352	0.750	0.072	0.414	135.2	5.8	E
173606	C 5	12.4	8.3	19.1	2.03	12.7	35.68	0.488	0.328	0.750	0.080	0.500	203.7	6.3	E

All characteristics are nominal