

# SE889/K2.2



- ✓ 100% KAYS compatible, applicable for most types of cranes
- ✓ Easy mounting and adaption
- ✓ Robust and reliable
- ✓ Redundant, monitored emergency stop
- ✓ Can be combined with all Gross Funk transmitter types
- ✓ Prototype tested
- ✓ VDV approved

Dimensions (LxWxH)mm	330x230x3110
Weight	6800gr
IP Protection Class	IP65
Automatic 12/24V Switch	12/24V DC 24/48/11 5/230 V AC
Operating temperature	-20 - +60°C
Safety class (DIN19250)	AK5
DIN rail assembly	✗
Aluminium receiver box	✓
Number of digital functions (basis equipment)	25
Number of analogue outputs per extension module	8
Number of PWM outputs per extension module	8
Number of digital inputs per extension module	16
Number of analogue inputs per extension module	2
Max. Resolution of the analogue inputs	12 BIT

Max. Resolution of the analogue outputs	12BIT
Serial interface (optional)	RS232, RS485
Serial interface (already on board)	
BUS capable (optional)	✓
Extendable	✓
Frequency switch	✓
Reflektomat	✓
Frequency hopping	✓
Transceiver (bi-direction) radio path	✓
Multiple transmitting operation	✓
Multiple receiving operation	✓
Receiver standby	✗
Adaptor for charger on receiver box	✓