

Eurobox trolley

Sturdy steel frame, platforms of sheet metal with a folded edge, adjustable at intervals of 280 mm. Outstandingly suitable for mounting Euroboxes (listed in part 96). Platforms can be secured in different positions and at inclinations of 15° and 30° for easier access to the boxes.

The bottom platform is fixed to the frame and cannot be inclined. Handle with Santoprene® coating and impact resistant polypropylene. 2 fixed wheels and 2 castors (with parking brake).

Colour: Silver **powder-coated.**

Note: Supplied for self-assembly, saving freight costs. Delivered unassembled.



Fitting example (supplied without the Euro standard bins).

Type		TE37
91 8587 Eurobox trolley		XXX
Height	mm	1735
Width	mm	1300
Depth	mm	670
Load face width	mm	1240
Platform area depth	mm	610
Load capacity per platform	kg	50
maximum load capacity	kg	250
Weight	kg	76

fetra... TPE tyres

Change of standard for the tyres:

New standard is TPE tyres. Of course, these leave no scuffing or tracking marks.



fetra... Totalstop – the FETRA central braking system

Very high braking effect on all tyre materials where the parking brake is made of rubber. Because the pedal has a large ground clearance, the brake is easily released. The brake pedal is within the operator's field of view at all times. The brake can be applied with the castor in any position. Simply by pressing the pedal, the rotation of the wheel and the swivelling of both castors is prevented.

Note: Additional charge option for the table trolley. To be delivered fitted to the table trolley. It cannot be retro-fitted. For all Fetra table trolleys **apart from** No. 919805 and No. 919808.



suitable for platform area	850X500	1000X600	1000X700	1200X800
91 9801 Totalstop braking system	XXX	XXX	XXX	XXX

fetra... Trolley with handle, load capacity 200 / 250 kg

Welded steel tubes, platform made of chipboard. 2 fixed wheels and 2 castors (with parking brake) and TPE tyres, hubs with grooved ball bearings.

Standard: EN 1757-3

Colour: Brilliant blue RAL 5007 **powder-coated.**

Note: Supplied for self-assembly, saving freight costs. Delivered unassembled.

Type		KF2	KF33
91 9805 Trolley with handle		XXX	XXX
Height	mm	860	910
Width	mm	890	860
Depth	mm	500	450
Load face width	mm		600
Platform area depth	mm	500	450
Height of bottom shelf	mm		195
Height of top shelf	mm	–	770
Wheel Ø	mm		125
Safe working load	kg	250	250
Weight	kg	12	19

