



Product name

## Set of universal 2- and 3-jaw pullers with extremely narrow jaws

For removing gears, bearings, sprockets, synchronizer bodies, etc., in tight or difficult-to-access spaces.

Art. No. K-2030-10-S-T

Series K-2030-10-S-T

EAN 4021176852022

	Technical attribute	Metric	Imperial
	Spread	120; 130 mm	4 3/4; 5 1/8 inch
	Depth	100 - 350 mm	3 7/8 - 13 3/4 inch
	Spread used internal	70 - 180 mm	2 3/4 - 7 1/8 inch
	Maximum torque	35 Nm	
	Maximum load	3 t	3 US t
	Weight	8.805 kg	
	Number of jaws	3	3




## Technologies



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



## Spare part

Art. No.	Product name
614160	Mechanical pressure spindle.
614250	Mechanical pressure spindle.
1-94-P	2 extremely narrow jaws (pair)
1-194-P	2 extremely narrow jaws (pair)
1-254-P	2 extremely narrow jaws (pair)
1-94-S	3 extremely narrow jaws (set)
1-194-S	3 extremely narrow jaws (set)
1-254-S	3 extremely narrow jaws (set)
20-10-SP-T	2-jaw puller with extremely narrow jaws, in set
20-10-T	2-jaw cross bar
30-10-T	Cross-beam

## Accessories

Art. No.	Product name
K-600-014	Set of interchangeable pressure pads for KUKKO pressure screws



## Content

<b>Art. No.</b>	<b>Product name</b>
20-10-SP-T	2-jaw puller with extremely narrow jaws, in set
30-10-T	Cross-beam
614250	Mechanical pressure spindle.
1-94-E	Jaws (individual)
1-194-E	Jaws, individual
1-254-E	Jaws, individual