






# ENCLOSED HOSE REELS FOR COMPRESSED AIR

Pressure PN. 12 bar	Temperature 70°C	Construction Epoxy-coated steel and stainless steel	Shockproof	Ergonomic Easy operation	Safety in use	Locking						
		A	B	Flow rate Without coupler l/min	Diameter ID/OD in mm	With coupling	Length m	Weight kg	Mounting bracket included	Swivel inlet	Outlet	REFERENCE
DGF series - Large industrial type - Polyurethane hose												
		520	462	500	8 x 14	IRM 06	10	17	Rigid	G 3/8 Female		DGF 0810
		520	462	350	8 x 14	IRM 06	15	18,5	Rigid	G 3/8 Female		DGF 0815
		520	462	260	8 x 14	IRM 06	20	20	Rigid	G 3/8 Female		DGF 0820
		520	462	900	10x17	IRM 06	10	18	Rigid	G 3/8 Female		DGF 1010
		520	462	700	10x17	IRM 06	15	19	Rigid	G 3/8 Female		DGF 1015
		520	462	1800	13x20	ISI 08	10	19	Rigid	G 1/2 M.		DGF 1310IS
DGF series - large - Polyurethane hose												
				Fixed bracket								
		520	462	520	8 x 14		10	17	Rigid	G 3/8 Female		DGF 0810N
		520	462	350	8 x 14		15	18.5	Rigid	G 3/8 Female		DGF 0815N
		520	462	260	8 x 14		20	20	Rigid	G 3/8 Female		DGF 0820N
		520	462	900	10x17		10	18	Rigid	G 3/8 Female		DGF 1010N
		520	462	700	13x20		10	19	Rigid	G 1/2 Male		DGF 1310N
520	462	700	10x17		15	19	Rigid	G 3/8 Female		DGF 1015N		
Swivel bracket for DGF hose reels												
				For DGF								DGF PIV