

# Product datasheet

Specifications



Venta V211T Globe Valve, 2-Way, PN16, Rp 1 1/4 Internal thread, DN32, 16 Kvs, Nodular Iron, Brass Plug.

7211736000

## Main

Valve product range	Venta
Product or component type	Valve
Valve type	Globe
Valve product series	V211T
Valve model	V211T/32/16
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Rp Internal
Valve connection size	Rp 1-1/4
Pipe size	32 mm
Body size	32 mm (1-1/4 in)
Flow characteristic	Equal percentage
Flow coefficient	18.5 cv 16 kvs
Pressure class	PN16
Operating fluid temperature	-20...120 °C
Pressure fluid max delta P normal life	399.90 kPa
Control valve rangeability	Greater than 50:1
Stroke length	20 mm
Seat leakage	Port A: Class IV-S1 (0.005 %)
Stem flow action	Stem up closed
Stem movement	Linear
Trim material	Brass
Body material	Nodular cast iron EN-JS 1030
Seat material	Port A: nodular cast iron EN-JS 1030
Stem material	Stainless steel AISI 303
Plug material	CW602N brass

Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A:EPDM (ethylene propylene diene monomer)
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. Australia.